



<b>ESSOR 163</b>	ORFS 3/8"	34,1	33,7	37,1	29,4	28,1	32,7
<b>ESSORTM 163</b>	ORFS 3/8"	37,5	37,0	40,9	32,3	30,9	36,0
<b>ESSOR 164</b>	ORFS 1/2"	34,1	33,7	37,1	29,4	28,1	32,7
<b>ESSORTM 164</b>	ORFS 1/2"	37,5	37,0	40,9	32,3	30,9	36,0
<b>ESSOR 165</b>	ORFS 5/8"	34,1	33,7	37,1	29,4	28,1	32,7
<b>ESSORTM 165</b>	ORFS 5/8"	37,5	37,0	40,9	32,3	30,9	36,0
<b>ESSOR 303</b>	ORFS 3/8"	60,0	59,2	65,1	51,5	49,2	57,3
<b>ESSORTM 303</b>	ORFS 3/8"	66,0	65,0	71,5	56,6	54,1	63,0
<b>ESSOR 304</b>	ORFS 1/2"	60,0	59,2	65,1	51,5	49,2	57,3
<b>ESSORTM 304</b>	ORFS 1/2"	66,0	65,0	71,5	56,6	54,1	63,0
<b>ESSOR 305</b>	ORFS 5/8"	60,0	59,2	65,1	51,5	49,2	57,3
<b>ESSORTM 305</b>	ORFS 5/8"	66,0	65,0	71,5	56,6	54,1	63,0
<b>ESSOD 164</b>	O-Ring 1/2"	34,1	33,7	37,1	29,4	28,1	32,7
<b>ESSODTM 164</b>	O-Ring 1/2"	37,5	37,0	40,9	32,3	30,9	36,0
<b>ESSOD 303</b>	O-Ring 3/8"	60,0	59,2	65,1	51,5	49,2	57,3
<b>ESSODTM 303</b>	O-Ring 3/8"	66,0	65,0	71,5	56,6	54,1	63,0
<b>ESSOD 305</b>	O-Ring 5/8"	60,0	59,2	65,1	51,5	49,2	57,3
<b>ESSODTM 305</b>	O-Ring 5/8"	66,0	65,0	71,5	56,6	54,1	63,0

(\*) Su Tutma Kapasiteleri ve Kurutabileceği Akışkan Miktarları ARI 710-2009 ve DIN 8948 standartlarını referans almaktadır.  
Water Adsorption Capacities and Weight of the Dehydratable Refrigerant are according to the ARI 710-2009 and DIN 8948