

ÖNERİLEN KAPASİTE ve BOYUTLAR TABLOSU / RECOMMENDED CAPACITY, DIMENSIONS TABLE

TIP TYPE	BAĞLANTI CONNECTION		BOYUTLAR DIMENSIONS (mm)			HACİM VOLUME (lt)	YAĞ ÖN YÜKLEME HACMİ OIL PRE CHARGE VOLUME (lt)	ÇALIŞMA SICAKLIĞI WORKING TEMPERATURE RANGE TS ° C (min. / max.)	MAKS. ÇALIŞMA BASINCI MAX. WORKING PRESSURE PS bar	NOMİNAL KAPASİTE NOMİNALCAPACITY (kw)			BASINÇLI KAP SINIFI PED CATEGORY
	in.	mm.	Ø	A	B					R134A	R404A / R507	R22 / R410A / R407C	
	ESSLA1S	ODS 1/2"	-	76	272					244	1,0	0,15	
ESSLA1S	-	12	76	272	244	1,0	0,15	-40 / +70	40	4,5	5,0	7,0	ART. 4.3
ESSLA1,5S	ODS 5/8"	16	76	382	354	1,5	0,2	-40 / +70	40	5,5	7,0	7,5	CAT. I
ESSLA1,5S	ODS 3/4"	19	76	382	354	1,5	0,2	-40 / +70	40	6,0	8,0	8,0	CAT. I
ESSLA2S	ODS 5/8"	16	102	325	295,5	2,0	0,25	-40 / +70	40	8,0	10,0	10,5	CAT. I
ESSLA2S	ODS 3/4"	19	102	325	295,5	2,0	0,25	-40 / +70	40	8,5	10,5	11,0	CAT. I
ESSLA2S	ODS 7/8"	22	102	325	295,5	2,0	0,25	-40 / +70	40	9,0	11,0	12,0	CAT. I
ESSLA4S	ODS 7/8"	22	139	344	326	4,0	0,5	-40 / +70	40	14,0	16,0	25,0	CAT. I
ESSLA4S	ODS 1-1/8"	28	139	344	326	4,0	0,5	-40 / +70	40	25,0	26,0	40,0	CAT. I
ESSLA4S	ODS 1-3/8"	35	139	344	326	4,0	0,5	-40 / +70	40	35,0	40,0	60,0	CAT. I
ESSLA7S	ODS 7/8"	22	168	400	383	7,0	0,8	-40 / +70	40	30,0	32,0	45,0	CAT. II
ESSLA7S	ODS 1-1/8"	28	168	400	383	7,0	0,8	-40 / +70	40	35,0	36,0	55,0	CAT. II
ESSLA7S	ODS 1-3/8"	35	168	400	383	7,0	0,8	-40 / +70	40	40,0	42,0	70,0	CAT. II
ESSLA10S	ODS 1-1/8"	28	219	367,5	342,5	10,0	1,0	-40 / +70	40	50,0	55,0	80,0	CAT. II
ESSLA10S	ODS 1-3/8"	35	219	367,5	342,5	10,0	1,0	-40 / +70	40	55,0	60,0	90,0	CAT. II
ESSLA10S	ODS 1-5/8"	42	219	367,5	342,5	10,0	1,0	-40 / +70	40	60,0	65,0	100,0	CAT. II
ESSLA20S	ODS 1-1/8"	28	219	650	610	20,0	1,5	-40 / +70	40	68,0	85,0	110,0	CAT. II
ESSLA20S	ODS 1-3/8"	35	219	650	610	20,0	1,5	-40 / +70	40	75,0	117,0	124,0	CAT. II
ESSLA20S	ODS 1-5/8"	42	219	650	610	20,0	1,5	-40 / +70	40	80,0	136,0	143,0	CAT. II
ESSLA30S	ODS 1-3/8"	35	273	639,5	609,5	30,0	3,0	-40 / +70	40	85,0	140,0	150,0	CAT. III
ESSLA30S	ODS 1-5/8"	42	273	639,5	609,5	30,0	3,0	-40 / +70	40	92,0	186,0	219,0	CAT. III
ESSLA30S	ODS 2-1/8"	54	273	639,5	609,5	30,0	3,0	-40 / +70	40	148,0	300,0	354,0	CAT. III
ESSLA30S	ODS 2-5/8"	67	273	639,5	609,5	30,0	3,0	-40 / +70	40	225,0	461,0	545,0	CAT. III
ESSLA35S	ODS 3-1/8"	80	273	732,5	713,5	35,0	3,0	-40 / +70	40	285,0	578,0	683,0	CAT. III
ESSLA35S	ODS 3-5/8"	92	273	732,5	713,5	35,0	3,0	-40 / +70	40	370,0	742,0	877,0	CAT. III